

Skirt Quiz

1. Before the skirt is sanded and ready to be cut, fitted and attached, what needs to be done to the cabinet?
 - a) The drawer needs to be completed and the decorative front needs to be attached and sanded.
 - b) The face frame needs to be attached and trimmed.
 - c) The bottom rail and bottom 6"-10" of the sides need to be sanded. The rail must not have any cross grain scratches in it and the face frame must be flush with the sides.

2. How far down from the top edge of the skirt does the glue need to start?
 - a) 1/4"
 - b) 1/2"
 - c) 1/8"
 - d) 3/4"

3. What is the joint called that is used to join the corners of the skirt?
 - a) Box joint
 - b) Biscuit joint
 - c) Dovetail joint
 - d) Miter joint

4. What length of nails are used to attach the skirt?
 - a) 7/8"
 - b) 1"
 - c) 1 1/4"
 - d) 1 1/2"

5. What saw is used to cut the joints?
 - a) Miter saw
 - b) Table saw
 - c) Radial arm saw
 - d) Jig saw

6. It is okay if glue squeezes out the top edge of the skirt because it can be cleaned off with a damp rag.
 - a) True
 - b) False

7. Why are miters used when joining the front piece and side pieces of the skirt?
 - a) UGH!!!- what?
 - b) To eliminate end grain
 - c) To make it difficult to keep up
 - d) None of the above

8. The style of edge detail that is on your skirt does not have to match the edge detail on your drawer front.
 - a) True
 - b) False

